

Monza ATF MVS

HC-Synthetic Automatic Transmission Fluid

Properties

- Very high viscosity index.
- High load carrying capacity and extremely wear-reducing.
- Low pour point.
- No foam formation.
- High thermal stability.
- Reliable friction coefficient characteristics.
- Excellent viscosity-temperature behaviour.
- Excellent oxidation stability.
- Neutral towards common sealing materials.

Application notes

- Automatic automotive transmission and torque converter.
- Hydrostatic transmissions.
- Power steering.
- Hydraulic systems.

Observe manufacturer's instructions!

Service description

Recommendations*:

- Aisin Warner JWS 3309
- Allison C-4, TES-295, TES-389
- BMW/Mini P/N 81 22 9 400 272/275, 81 22 9 407 858/859
83 22 0 024 249/359, 83 22 0 026 922 (BMW 7045 E)
83 22 0 402 413, 83 22 0 403 248/249
83 22 7 542 290, 83 22 9 407 765 (BMW LA 2634)
- Chrysler/Dodge/Jeep AS68RC ATF
and ATF+2/ ATF+3/ ATF+4, SP-III
- DTFR 38B100 (236.3)/ 13C110 (236.11)/ 13C140 (236.7)
and 13C150 (236.8)/ 13C170 (236.9)/ 13C180 (236.91)
- MB 236.5/ 236.6/ 236.10
- Ford WSS-M2C 919-E (Mercon V)
- Ford/Lincoln/Mercury P/N XT-2-QDX [M], XT-2-QSM [Syn]
XT-5-QM or -DM [V], XT-8-QAW [Premium]
XT-9-QMM5 [FNR5], WSS-M2C 922-A1
- GM Dexron II/ II-D/ II-E/ III-G/ III-H
- GM/GMC/Opel/Saturn P/N 19 40 700/767
21005966 (transaxle), 22717466, 88900925/ 9986195
and T-IV, Type A Suffix A
- Jaguar JLM 20238/ 20292/ 21044/ K17
- Jaguar WSS-M2C 922-A1
- Land Rover Texaco ETL-7045 E
- MAN 339 A
- Mercon V
- Mobil ATF 3309

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.

Recommendations* (following):

- Porsche P/N 000 043 204 41, 000 043 205 09 and 999 917 547 00 (A2)
- PSA Peugeot Citroen P/N Z 000169756
- Renault Matic D2
- Renk Genuine Oil
- Saab 3309 T-IV
- Shell 3403-M115, LA 2634
- Texaco ETL 7045E/ 8072B and N402
- Voith H55.6335.XX, Svc Bltn # 013/ 118
- Volvo P/N 1161521, 1161540/ 1161640, 1273.41
- VW/Audi G 052 025 A2, G 052 055, G 052 162 (A1, A2) G 052 990 (A2), G 055 025 (A2), US 000 162
- ZF TE-ML 11A/ 11B

TYPICAL PARAMETERS	METHODS	UNITS	Monza ATF MVS
Density at 15°C	DIN ISO 51562	g/cm ³	0.850
Viscosity at 40°C	DIN 51 562	mm ² /s	38.5
Viscosity at 100°C	DIN 51 562	mm ² /s	7.1
Viscosity index (VI)	DIN ISO 2909	-	150
Pour point	ASTM D 7346	°C	-45
Flash point COC	DIN ISO 2592	°C	224
Colour	-	-	red / yellow

November 2023

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.

ID 0730-0735

MITAN Mineralöl GmbH

Industriestr. 8 • 49577 Ankum • Tel.: 05462/747050 • Fax: 05462/747033
www.mitan-oil.de